

PK043-WST10



Display	Size	4.3" diagonal (16:9)
	Max. Resolution	480 x 272
	Type	TFT LCD
	Max. Colors	TFT True Color ; 65536 Colori
	Backlight Type	LED
	Backlight Life (hr)	20000
	Display Contrast	500
	Luminance (cd/m2)	250
	Operation	RTOS
	Touch Panel	4 Wire Analog Touch Panel
	CPU	CPU RISC ARM 32Bit 200MHz
	Backup SRAM	128 KB
	Working Memory	32 MB
	Built-in Storage	8 MB (NOR Flash)
Real Time Clock (RTC)	Yes	
Communication Interface	Micro-SD Slot	No
	USB Client	Yes
	USB Host	Yes
	Serial	COM1 RS232/RS422/RS485
		COM2 -
COM3 RS485		
Ethernet	N.A	
Power	Supply Voltage	24VDC±10% Isolated
	Consumption	6W
Environment	Operating Temperature	0°~50°
	Relative Humidity	10%~90%
	Ingress Protection	IP65
	Cooling	Natural Cooling
Dimension	Dimension WxHxD (mm)	130.0 x 106.2 x 39
	Cutout Dimension WxH (mm)	119.0 x 93.0
	Net Weight (kg)	0.35 KG

PK043-WST30



Display	Size	4.3" diagonal (16:9)
	Max. Resolution	480 x 272
	Type	TFT LCD
	Max. Colors	TFT True Color ; 65536 Colori
	Backlight Type	LED
	Backlight Life (hr)	20000
	Display Contrast	500
	Luminance (cd/m2)	250
	Operation	RTOS
	Touch Panel	4 Wire Analog Touch Panel
	CPU	CPU RISC ARM 32Bit 200MHz
	Backup SRAM	128 KB
	Working Memory	32 MB
	Built-in Storage	8 MB (NOR Flash)
Real Time Clock (RTC)	Yes	
Communication Interface	Micro-SD Slot	No
	USB Client	Yes
	USB Host	Yes
	Serial	COM1 RS232/RS422/RS485
		COM2 -
COM3 RS485		
Ethernet	Yes	
Power	Supply Voltage	24VDC±10% Isolated
	Consumption	6W
Environment	Operating Temperature	0°~50°
	Relative Humidity	10%~90%
	Ingress Protection	IP65
	Cooling	Natural Cooling
Dimension	Dimension WxHxD (mm)	130.0 x 106.2 x 39
	Cutout Dimension WxH (mm)	119.0 x 93.0
	Net Weight (kg)	0.35 KG

PK070-WST40



Display	Size	7" diagonal (16 : 9)
	Max. Resolution	800 x 480
	Type	TFT LCD
	Max. Colors	TFT True Color ; 65536 Colori
	Backlight Type	LED
	Backlight Life (hr)	20000
	Display Contrast	500
	Luminance (cd/m2)	250
	Operation	RTOS
	Touch Panel	4 Wire Analog Touch Panel
	CPU	CPU RISC ARM 32Bit 200MHz
	Backup SRAM	128 KB
	Working Memory	32 MB
	Built-in Storage	8 MB (NOR Flash) + 128 MB (NAND Flash)
Real Time Clock (RTC)	Yes	
Communication Interface	Micro-SD Slot	No
	USB Client	Yes
	USB Host	Yes
	Serial	COM1 RS232/RS422/RS485
		COM2 -
COM3 RS485		
Ethernet	Yes	
Power	Supply Voltage	24VDC±10% Isolated
	Consumption	10W
Environment	Operating Temperature	0°~50°
	Relative Humidity	10%~90%
	Ingress Protection	IP65
	Cooling	Natural Cooling
Dimension	Dimension WxHxD (mm)	204.4 x 151.0 x 33
	Cutout Dimension WxH (mm)	191.5 x 138.0
	Net Weight (kg)	0.65 KG

PK100-WST40



Display	Size	10.1" diagonal (16 : 9)
	Max. Resolution	1024 x 600
	Type	TFT LCD
	Max. Colors	TFT True Color ; 65536 Colori
	Backlight Type	LED
	Backlight Life (hr)	20000
	Display Contrast	500
	Luminance (cd/m2)	180
	Operation	RTOS
	Touch Panel	4 Wire Analog Touch Panel
	CPU	CPU RISC ARM 32Bit 200MHz
	Backup SRAM	128 KB
	Working Memory	32 MB
	Built-in Storage	8 MB (NOR Flash) + 128 MB (NAND Flash)
Real Time Clock (RTC)	Yes	
Communication Interface	Micro-SD Slot	No
	USB Client	Yes
	USB Host	Yes
	Serial	COM1 RS232/RS422/RS485
		-
	COM3 RS485	
Ethernet	YES(10/100Mbps)	
Power	Supply Voltage	24VDC±10% Isolated
	Consumption	20W
Environment	Operating Temperature	0°~50°
	Relative Humidity	10%~90%
	Ingress Protection	IP65
	Cooling	Natural Cooling
Dimension	Dimension WxHxD (mm)	270.1 x 212.1 x 42.5
	Cutout Dimension WxH (mm)	259.5 x 201.5
	Net Weight (kg)	1.1 KG

PK2043-30ST



Display	Size	4,3" diagonal
	Max. Resolution	480 x 272
	Type	TFT LCD
	Max. Colors	16-bit
	Backlight Type	LED
	Backlight Life (hr)	20000
	Display Contrast	700
	Luminance (cd/m2)	350
	Touch Panel	4 Wire Analog Touch Panel
	CPU	CPU RISC ARM9 32Bit
	Backup SRAM	128 KB
	Working Memory	64 MB
	Built-in Storage	64 MB (NAND Flash)
	Real Time Clock (RTC)	Yes
Communication Interface	Micro-SD Slot	N/A
	USB Client	Yes
	USB Host	Yes
	Serial (5-Pin)	COM1 RS232
		COM2 RS422/RS485
COM3 RS485		
Ethernet	N.A.	
Power	Supply Voltage	24VDC±10% Isolated
	Consumption	20W
Environment	Operating Temperature	-10°~60°
	Relative Humidity	10%~90%
	Ingress Protection	IP65
	Cooling	Natural Cooling
Dimension	Dimension WxHxD (mm)	129 x 103 x 33
	Cutout Dimension WxH (mm)	119 x 93
	Net Weight (kg)	0.33 KG

PK2043-31ST



Display	Size	4,3" diagonal
	Max. Resolution	480 x 272
	Type	TFT LCD
	Max. Colors	16-bit
	Backlight Type	LED
	Backlight Life (hr)	20000
	Display Contrast	700
	Luminance (cd/m2)	350
	Touch Panel	4 Wire Analog Touch Panel
	CPU	CPU RISC ARM9 32Bit
	Backup SRAM	128 KB
	Working Memory	64 MB
	Built-in Storage	64 MB (NAND Flash)
	Real Time Clock (RTC)	Yes
Communication Interface	Micro-SD Slot	N.A.
	USB Client	Yes
	USB Host	Yes
	Serial (5-Pin)	COM1 RS232
		COM2 RS422/RS485
COM3 RS485		
Ethernet	YES(10/100 Mbps).	
Power	Supply Voltage	24VDC±10% Isolated
	Consumption	20W
Environment	Operating Temperature	-10°~60°
	Relative Humidity	10%~90%
	Ingress Protection	IP65
	Cooling	Natural Cooling
Dimension	Dimension WxHxD (mm)	129 x 103 x 33
	Cutout Dimension WxH (mm)	119 x 93
	Net Weight (kg)	0.33 KG

PK2070-31ST



Display	Size	7" diagonal
	Max. Resolution	800 x 480
	Type	TFT LCD
	Max. Colors	16-bit
	Backlight Type	LED
	Backlight Life (hr)	20000
	Display Contrast	700
	Luminance (cd/m2)	350
	Touch Panel	4 Wire Analog Touch Panel
	CPU	CPU RISC ARM9 32Bit
	Backup SRAM	128 KB
	Working Memory	64 MB
	Built-in Storage	64 MB (NAND Flash)
	Real Time Clock (RTC)	Yes
Communication Interface	Micro-SD Slot	N.A.
	USB Client	Yes
	USB Host	Yes
	Serial (DB9)	COM1 RS232
		COM2 RS422/RS485
COM3 RS485		
Ethernet	YES(10/100 Mbps)	
Power	Supply Voltage	24VDC±10% Isolated
	Consumption	20W
Environment	Operating Temperature	-10°~60°
	Relative Humidity	10%~90%
	Ingress Protection	IP65
	Cooling	Natural Cooling
Dimension	Dimension WxHxD (mm)	204.4 x 151 x 33
	Cutout Dimension WxH (mm)	191.5 x 138
	Net Weight (kg)	0.55 KG

PK2100-31ST



Display	Size	10.1" diagonal
	Max. Resolution	1024 x 600
	Type	TFT LCD
	Max. Colors	16-bit
	Backlight Type	LED
	Backlight Life (hr)	20000
	Display Contrast	700
	Luminance (cd/m2)	250
	Touch Panel	4 Wire Analog Touch Panel
	CPU	CPU RISC ARM9 32Bit
	Backup SRAM	128 KB
	Working Memory	64 MB
	Built-in Storage	64 MB (NAND Flash)
	Real Time Clock (RTC)	Yes
Communication Interface	Micro-SD Slot	N.A.
	USB Client	Yes
	USB Host	Yes
	Serial (DB9)	COM1 RS232
		COM2 RS422/RS485
		COM3 RS485
Ethernet	YES(10/100 Mbps)	
Power	Supply Voltage	24VDC±10% Isolated
	Consumption	20W
Environment	Operating Temperature	-10°~60°
	Relative Humidity	10%~90%
	Ingress Protection	IP65
	Cooling	Natural Cooling
Dimension	Dimension WxHxD (mm)	270.1 x 212.1 x 42.5
	Cutout Dimension WxH (mm)	259.5 x 201.5
	Net Weight (kg)	1.2 KG

PK2121-31ST



Display	Size	12.1" diagonal
	Max. Resolution	1024 x 768
	Type	TFT LCD
	Max. Colors	16-bit
	Backlight Type	LED
	Backlight Life (hr)	20000
	Display Contrast	700
	Luminance (cd/m2)	500
	Touch Panel	4 Wire Analog Touch Panel
	CPU	CPU RISC ARM9 32Bit
	Backup SRAM	128 KB
	Working Memory	64 MB
	Built-in Storage	64 MB (NAND Flash)
	Real Time Clock (RTC)	Yes
Communication Interface	Micro-SD Slot	N/A
	USB Client	Yes
	USB Host	Yes
	Serial (DB9)	COM1 RS232
		COM2 RS422/RS485
COM3 RS485		
Ethernet	YES(10/100Mbps)	
Power	Supply Voltage	24VDC±10% Isolated
	Consumption	20W
Environment	Operating Temperature	-10°~60°
	Relative Humidity	10%~90%
	Ingress Protection	IP65
	Cooling	Natural Cooling
Dimension	Dimension WxHxD (mm)	335.4 x 245.9 x 58.2
	Cutout Dimension WxH (mm)	302 x 228
	Net Weight (kg)	2 KG

PK2150-31ST



Display	Size	15" diagonal (4 : 3)
	Max. Resolution	1024 x 768
	Type	TFT LCD
	Max. Colors	16-bit
	Backlight Type	LED
	Backlight Life (hr)	20000
	Display Contrast	700
	Luminance (cd/m2)	350
	Touch Panel	4 Wire Analog Touch Panel
	CPU	CPU RISC ARM9 32Bit
	Backup SRAM	128 KB
	Working Memory	64 MB
	Built-in Storage	128 MB (NAND Flash)
	Real Time Clock (RTC)	Yes
Communication Interface	Micro-SD Slot	N/A
	USB Client	Yes
	USB Host	Yes
	Serial (DB9)	COM1 RS232
		COM2 RS422/RS485
		COM3 RS485
Ethernet	YES(10/100Mbps)	
Power	Supply Voltage	24VDC±10% Isolated
	Consumption	20W
Environment	Operating Temperature	-10°~60°
	Relative Humidity	10%~90%
	Ingress Protection	IP65
	Cooling	Natural Cooling
Dimension	Dimension WxHxD (mm)	399.1 x 297.6 x 57.5
	Cutout Dimension WxH (mm)	384.5 x 283.0
	Net Weight (kg)	3 KG