

GX607-WST4B



Display	Size	7" diagonal (16 : 9)	
	Max. Resolution	800 x 480	
	Type	TFT LCD	
	Max. Colors	TFT True Color ; 65536 Colori	
	Backlight Type	LED	
	Backlight Life (hr)	20000	
	Display Contrast	500	
	Luminance (cd/m2)	300	
	Operation	RTOS	
	Touch Panel	4 Wire Analog Touch Panel	
	CPU	ARM11 RISC 667/800MHz	
	Backup SRAM	1 MB	
	Working Memory	512 MB	
	Built-in Storage	1 GB (64MB: Win CE OS 6.0 R3)	
Real Time Clock (RTC)	Yes		
Communication Interface	Micro-SD Slot	Yes	
	USB Client	Yes	
	USB Host	Yes	
	Serial	COM1	RS232/RS422/RS485
		COM2	RS232/RS485
		COM3	RS232
	Ethernet	Yes (10/100Mbps)	
	Audio	N.A	
Microphone in	N.A		
Video	N.A		
Power	Supply Voltage	24VDC±10% Isolated	
	Consumption	13W	
Environment	Operating Temperature	-20°~60°	
	Relative Humidity	10%~90%	
	Ingress Protection	IP66	
	Frame	Plastic (aluminum optional)	
	Cooling	Natural Cooling	
Dimension	Dimension WxHxD (mm)	188.0 x 143.3 x 36.1	
	Cutout Dimension WxH (mm)	175.0 x 132.6	
	Net Weight (kg)	0.65 KG	

GX608-TST4B



Display	Size	8" diagonal (4 : 3)
	Max. Resolution	800 x 600
	Type	TFT LCD
	Max. Colors	TFT True Color ; 65536 Colori
	Backlight Type	LED
	Backlight Life (hr)	20000
	Display Contrast	500
	Luminance (cd/m2)	250
	Operation	RTOS
	Touch Panel	4 Wire Analog Touch Panel
	CPU	ARM11 RISC 667/800MHz
	Backup SRAM	1 MB
	Working Memory	512 MB
	Built-in Storage	1 GB (64MB: Win CE OS 6.0 R3)
	Real Time Clock (RTC)	Yes
Communication Interface	Micro-SD Slot	Yes
	USB Client	Yes
	USB Host	Yes
	Serial	COM1 RS232/RS422/RS485
		COM2 RS232/RS485
COM3 RS232		
Ethernet	YES(10/100Mbps)	
Power	Supply Voltage	24VDC±10% Isolated
	Consumption	20W
Environment	Operating Temperature	0°~50°
	Relative Humidity	10%~90%
	Ingress Protection	IP66
	Frame	Plastic (aluminum optional)
Cooling	Natural Cooling	
Dimension	Dimension WxHxD (mm)	231.5 x 174.5 x 42.5
	Cutout Dimension WxH (mm)	221.0 x 164.0
	Net Weight (kg)	0.93 KG

GX610-TST4B



Display	Size	10.4" diagonal (4 : 3)
	Max. Resolution	800 x 600
	Type	TFT LCD
	Max. Colors	TFT True Color ; 65536 Colori
	Backlight Type	LED
	Backlight Life (hr)	20000
	Display Contrast	400
	Luminance (cd/m2)	400
	Operation	RTOS
	Touch Panel	4 Wire Analog Touch Panel
	CPU	ARM11 RISC 667/800MHz
	Backup SRAM	1 MB
	Working Memory	512 MB
	Built-in Storage	1 GB (64MB: Win CE OS 6.0 R3)
	Real Time Clock (RTC)	Yes
Communication Interface	Micro-SD Slot	Yes
	USB Client	Yes
	USB Host	Yes
	Serial	COM1 RS232/RS422/RS485
		COM2 RS232/RS485
COM3 RS232		
Ethernet	YES(10/100Mbps)	
Power	Supply Voltage	24VDC±10% Isolated
	Consumption	20W
Environment	Operating Temperature	0°~50°
	Relative Humidity	10%~90%
	Ingress Protection	IP66
	Frame	Plastic (aluminum optional)
	Cooling	Natural Cooling
Dimension	Dimension WxHxD (mm)	270.1 x 212.1 x 42.5
	Cutout Dimension WxH (mm)	259.5 x 201.5
	Net Weight (kg)	1.2 KG

GX612-XSD4B



Display	Size	12.1" diagonal (4 : 3)	
	Max. Resolution	1024 x 768	
	Type	TFT LCD	
	Max. Colors	TFT True Color ; 65536 Colori	
	Backlight Type	LED	
	Backlight Life (hr)	20000	
	Display Contrast	500	
	Luminance (cd/m2)	600	
	Operation	RTOS	
	Touch Panel	4 Wire Analog Touch Panel	
	CPU	ARM11 RISC 667/800MHz	
	Backup SRAM	1 MB	
	Working Memory	512 MB	
	Built-in Storage	1 GB (64MB: Win CE OS 6.0 R3)	
Real Time Clock (RTC)	Yes		
Communication Interface	Micro-SD Slot	Yes	
	USB Client	Yes	
	USB Host	Yes	
	Serial	COM1	RS232/RS422/RS485
		COM2	RS232/RS485
		COM3	RS232
Ethernet	YES(10/100Mbps)		
Power	Supply Voltage	24VDC±10% Isolated	
	Consumption	20W	
Environment	Operating Temperature	0°~50°	
	Relative Humidity	10%~90%	
	Ingress Protection	IP66	
	Frame	Aluminum	
	Cooling	Natural Cooling	
Dimension	Dimension WxHxD (mm)	315.0 x 241.0 x 54.5	
	Cutout Dimension WxH (mm)	301.5 x 228.0	
	Net Weight (kg)	2.1 KG	

GX615-XSD4B



Display	Size	15" diagonal (4 : 3)
	Max. Resolution	1024 x 768
	Type	TFT LCD
	Max. Colors	TFT True Color ; 65536 Colori
	Backlight Type	LED
	Backlight Life (hr)	50000
	Display Contrast	700
	Luminance (cd/m2)	350
	Operation	RTOS
	Touch Panel	4 Wire Analog Touch Panel
	CPU	ARM11 RISC 667/800MHz
	Backup SRAM	1 MB
	Working Memory	512 MB
	Built-in Storage	1 GB (64MB: Win CE OS 6.0 R3)
	Real Time Clock (RTC)	Yes
Communication Interface	Micro-SD Slot	Yes
	USB Client	Yes
	USB Host	Yes
	Serial	COM1 RS232/RS422/RS485
		COM2 RS232/RS485
		COM3 RS232
Ethernet	YES(10/100Mbps)	
Power	Supply Voltage	24VDC±10% Isolated
	Consumption	15W
Environment	Operating Temperature	0°~50°
	Relative Humidity	10%~90%
	Ingress Protection	IP66
	Frame	Plastic (aluminum optional)
	Cooling	Natural Cooling
Dimension	Dimension WxHxD (mm)	399.1 x 297.6 x 55
	Cutout Dimension WxH (mm)	384.5 x 283.0
	Net Weight (kg)	2.68 KG