

PX070-WST4B



Display	Size	7" diagonal (16 : 9)
	Max. Resolution	800 x 600
	Type	TFT LCD
	Max. Colors	TFT True Color ; 65536 Colori
	Backlight Type	LED
	Backlight Life (hr)	20000
	Display Contrast	500
	Luminance (cd/m2)	300
	Operation	RTOS
	Touch Panel	4 Wire Analog Touch Panel
	CPU	ARM11 RISC 800 Mhz
	Backup SRAM	1 MB
	Working Memory	256 MB
	Built-in Storage	1 GB
	Real Time Clock (RTC)	Yes
Communication Interface	Micro-SD Slot	Yes
	USB Client	Yes
	USB Host	Yes
	Serial	COM1 RS232/RS422/RS485
		COM2 RS232/RS485
COM3 RS232		
Ethernet	YES(10/100Mbps)	
Power	Supply Voltage	24VDC±10% Isolated
	Consumption	13W
Environment	Operating Temperature	-20°~ +60°
	Relative Humidity	10%~90%
	Ingress Protection	IP66
	Cooling	Natural Cooling
Dimension	Dimension WxHxD (mm)	213.6 x 158.6 x 40.5
	Cutout Dimension WxH (mm)	192.0 x 138.5
	Net Weight (kg)	0.8 KG

PX104-TST4B



Display	Size	10.4" diagonal (4 : 3)
	Max. Resolution	800 x 600
	Type	TFT LCD
	Max. Colors	16-bit/18-bit (Software Selectable)
	Backlight Type	LED
	Backlight Life (hr)	20000
	Display Contrast	400
	Luminance (cd/m ²)	400
	Operation	RTOS
	Touch Panel	4 Wire Analog Touch Panel
	CPU	RISC ARM11 800MHz
	Backup SRAM	1MB
	Working Memory	256MB
	Built-in Storage	1GB (SLC Type)
Real Time Clock (RTC)	Yes	
Communication Interface	Micro-SD Slot	Yes
	USB Client	Yes
	USB Host	Yes
	Serial	COM1 RS232/RS422/RS485
		COM2 RS232/RS485
COM3 RS232		
Ethernet	YES(10/100Mbps)	
Power	Supply Voltage	24VDC±10% Isolated
	Consumption	15W
Environment	Operating Temperature	-20°~+60°
	Relative Humidity	10%~90%
	Ingress Protection	IP66
	Cooling	Natural Cooling
Dimension	Dimension WxHxD (mm)	280.3 x 222.3 x 45
	Cutout Dimension WxH (mm)	259.5 x 201.5
	Net Weight (kg)	1.25 KG

PX121-XSD4B



Display	Size	12.1" diagonal (4 : 3)
	Max. Resolution	1024 x 768
	Type	TFT LCD
	Max. Colors	16-bit/24-bit (Software selectable)
	Backlight Type	LED
	Backlight Life (hr)	50000
	Display Contrast	700
	Luminance (cd/m2)	600
	Operation	RTOS
	Touch Panel	5 Wire Analog Touch Panel
	CPU	800 Mhz ARM11 RISC
	Backup SRAM	1 MB
	Working Memory	256 MB
	Built-in Storage	1 GB (SLC Type)
Real Time Clock (RTC)	Yes	
Communication Interface	Micro-SD Slot	Yes (SDHC)
	USB Client	Yes
	USB Host	Yes
	Serial	COM1 RS232/RS422/RS485
		COM2 RS232/RS485
COM3 RS232 (RTS/CTS)		
Ethernet	YES(10/100Mbps)	
Power	Supply Voltage	24VDC±10% Isolated
	Consumption	20W
Environment	Operating Temperature	-20°~ 60°
	Relative Humidity	10%~90%
	Ingress Protection	IP66
	Cooling	Natural Cooling
Dimension	Dimension WxHxD (mm)	351.35 x 244.0 x 58.6
	Cutout Dimension WxH (mm)	301.5 x 228.0
	Net Weight (kg)	1.9 KG

PX150-XSD4B



Display	Size	15" diagonal (4 : 3)
	Max. Resolution	1024 x 768
	Type	TFT LCD
	Max. Colors	TFT True Color ; 65536 Colori
	Backlight Type	LED
	Backlight Life (hr)	50000
	Display Contrast	700
	Luminance (cd/m2)	350
	Operation	RTOS
	Touch Panel	5 Wire Analog Touch Panel
	CPU	CPU RISC ARM11 800MHZ
	Backup SRAM	1 MB
	Working Memory	256 MB
	Built-in Storage	1 GB
Real Time Clock (RTC)	Yes	
Communication Interface	Micro-SD Slot	Yes
	USB Client	Yes
	USB Host	Yes
	Serial	COM1 RS232/RS422/RS485
		COM2 RS232/RS485
COM3 RS232		
Ethernet	YES(10/100Mbps)	
Power	Supply Voltage	24VDC±10% Isolated
	Consumption	20W
Environment	Operating Temperature	-20°~60°
	Relative Humidity	10%~90%
	Ingress Protection	IP66
	Cooling	Natural Cooling
Dimension	Dimension WxHxD (mm)	399.1 x 297.6 x 55
	Cutout Dimension WxH (mm)	384.5 x 283.0
	Net Weight (kg)	2.68 KG